

REVERE

Rustic Appeal SPA74

PRODUCT SPECIFICATIONS

STYLE NAME:	Rustic Appeal SPA74
Plank/Tile Dimensions:	7 ½" x 54 11/32" x 12 mm
Strips Per Plank:	Single
Pieces per Carton:	6
Pattern Repeat	10
Sq. Ft. per Carton:	16.93
Cartons per Pallet:	50
Weight per Carton:	37.20 lbs
Profile:	UniClic® Technology
Surface Appearance:	Embossed in Register
Finish:	Aluminum Oxide
Finish Rating:	AC3 and AC4 see below
Core:	HDF (High Density Fiberboard)
Edges/Ends:	Micro Beveled Edges / Micro Beveled Ends
Attached Underlayment:	No
Warranty:	Limited Lifetime Residential Finish Warranty 5 year light to medium Commercial Finish Warranty
Installation Approved:	Floating Only - On, Above or Below Grade
ASTM E662-09 Smoke Density (Flaming)	Passes - 450 or Less
ASTM E648-10 Radiant Panel	Meets or exceeds Class 1
ASTM C1028-96 Static Coefficient of Friction	0.58 Dry
Impact Resistance	Passes Class 4 Heavy Commercial
Cleanability-Stain Resistance	Nalfa 3.4 Passes Class 4 Heavy Commercial
Xenon Light Resistance	Nalfa 3.3 Passes 5.0 Class 4
Thickness Swell	Nalfa 3.2 Passes Class 4 Heavy Commercial
Radiant Flux	Passes ASTM E648-08
Static Coefficient of Friction	Nalfa 3.1 Passes Class 4 Heavy Commercial
Surface Bond	Nalfa 3.10 Passes Class 4 Heavy Commercial

Colors		AC Rating	Quarter Round MQND	Incizo 5 in 1 MINCS	Incizo Base Stair Nose	Stair Nose MSNP
Fawn Chestnut	01	4	MQND-02945	MINCS-02945	5BASE-BASE03	MSNP-02945
Cedar Chestnut	02	4	MQND-01668	MINCS-01428	5BASE-BASE03	MSNP-01428
Knotted Chestnut	03	4	MQND-02863	MINCS-01575	5BASE-BASE03	MSNP-01575
Earthen Chestnut	04	4	MQND-01960	MINCS-01013	5BASE-BASE03	MSNP-01013
Sandcastle Oak	05	3	MQND-01936	MINCS-01667	5BASE-BASE03	MSNP-01667
Driftwood Oak	06	3	MQND-02627	MINCS-01574	5BASE-BASE03	MSNP-01574

Last Update 3/17/17 TC

We reserve the right without prior notification, to modify specifications, or substitute components as technological advancements or process improvements become available which improve the products performance. Please contact your Spartan Surfaces rep with any questions.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Check www.revere-flooring.com for a copy of our most recent installation instructions before beginning installation.

Complies with California ATCM 93120 (CARB) Emission Requirements
U.S. Lacey Act Compliant
FloorScore Certified*
***Contributes to LEED points**