

REVERE



TWO-STEP



SKILLFULLY SET

TWO-STEP AND SKILLFULLY SET

Two-Step features a linear pattern that demonstrates a unique long rolling wrap of colored yarns that display a 'Fade in Fade out' visual. Skillfully Set showcases a weaved visual common to many world cultures, which creates a timeless and handmade visual effect.

TWO-STEP


Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	15 oz/yd ² (509 g/m ²)
Pile Thickness	.076" (1.93 mm)
Stitches Per Inch	12.5 (49.21 per 10 cm)
Density	7,200
Weight Density	109,440
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Protection Plus Stain
Soil Release Technology	Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum of 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Installation Method	Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic / Multi Directional
Indoor Air Quality	Green Label Plus Certified # 1098
Size/Width	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants Warranty

SKILLFULLY SET


Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	15 oz/yd ² (509 g/m ²)
Pile Thickness	.068" (1.72 mm)
Stitches Per Inch	12.5 (49.21 per 10 cm)
Density	8,047
Weight Density	122,144
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Protection Plus Stain
Soil Release Technology	Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum of 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Installation Method	Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic / Multi Directional
Indoor Air Quality	Green Label Plus Certified # 1098
Size/Width	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants Warranty

Cover: Two-Step Carpet Tile 979 Reflective Symmetry and Skillfully Set Carpet Tile 979 Reflective Symmetry

Two-Step



Skillfully Set



Up to 2,000 sq. yds. available within 10 business days or less