


2mm / 12 mil Glue Down

TECHNICAL

ASTM F970	Static Load Limit	Passes
ASTMF925	Chemical Resistance	Passes
ASTM E648	Critical Radiant Flux	Class 1, >.45 w/cm ²
ASTM E662	Smoke Density	Passes, <450
ASTM F1515	Light Stability	Passes
ASTM F510	Wear Resistance	Wear Group: T
ASTM F2199	Dimensional Stability	Passes
ASTM F1914	Residual Indentation	Passes
DIN 51130	Slip Resistance	R10

FEATURES AND BENEFITS

- * 7 Year Light Commercial Warranty
- * 20 Year Residential Warranty
- * Durability, dependability and trendy colors make Broadstreet LVT the right choice
- * Broadstreet LVT has an enhanced polyurethane finish that provides superior scratch, scuff and stain resistance
- * Cost effective LVT option that meets the needs of many flooring projects
- * FloorScore® Certified 

PACKAGING


* Size	Nominal 7" x 48" Planks, Square Edge
* Gauge	2mm
* Wear Layer	12 mil
* Finish	Enhanced Polyurethane Coating
* Method of Install	Glue Down
* Carton Quantity	22 pieces per carton (51.39 sf/ctn)
* Item/Color Identifier	B212-###

3mm / 20 mil Glue Down

TECHNICAL

ASTM F970	Static Load Limit	Passes
ASTMF925	Chemical Resistance	Passes
ASTM E648	Critical Radiant Flux	Class 1, >.45 w/cm ²
ASTM E662	Smoke Density	Passes, <450
ASTM F1515	Light Stability	Passes
ASTM F510	Wear Resistance	Wear Group: T
ASTM F2199	Dimensional Stability	Passes
ASTM F1914	Residual Indentation	Passes
DIN 51130	Slip Resistance	R10

FEATURES AND BENEFITS

- * Lifetime Residential Warranty
- * 10 Year Commercial Warranty
- * Thicker construction, better suited for hiding subfloor Imperfections
- * 20 mil wear layer for increased stain, scratch and wear resistance
- * Floor Score Certified 

PACKAGING

* Size	Nominal 7" x 48" Planks, Square Edge
* Gauge	3mm
* Wear Layer	20 mil
* Finish	Enhanced Polyurethane Coating
* Method Of Install	Glue Down
* Carton Quantity	15 pieces per carton (35.04 sf/ctn)
* Item/Color Identifier	B320-###

